



MULTIPURPOSE BREAD OVEN



Modular Design

- * A wide range of option to choose from. Single, Double, Tripple deck options with or without fermentation cabinets and benches.
- * You can start small with one deck and work your way up to 3 decks as your business grows.
- * Independent Control and Wiring for Each Deck
- * Modular design makes it easier to re-locate the oven.

User-Friendly Control Panel

- * Precise Heat Control
- * In-Built Timer
- Turbo-mode for meeting daily challenges and operations
- * The Electronic Panel is cooled and well-insulated making it durable.
- * Temperatures reaching up to 400 Centigrad Degrees

Heat Consistency and Utmost Control

- * Front/ rear upper and lower heating elements are controlled seperately.
- * Upper Heating Elements are placed in ceramic tubes for the heat consistency.
- * 90 mm insulation and Italian-made claystones making sure that the oven is heat-consistent and energy efficient.

Options

- * Steam Option for wider range of applications .

Design

- * Bottom Opening Door
- * Double in-door lights per deck
- * Doors are equipped with heat-isolating glass.
- * Robust Legs with caster wheels

Applications

- * Pizza, Breads, Baklava, Bakery and Pastry products.

TECHNICAL SPECS

MODEL	MT-1400-2	MD-1400-2	MD-1400-1	ME-1400_1	ME 1400
EXTERIOR DIMENSIONS (x-y-z cm)	166 x 140 x 217	166 x 140 x 193	166 x 140 x 193	166 x 140 x 169	166 x 140 x 44
INTERNAL DIMENSIONS (X-y-z cm)	3 x 124 x 92 x 23	2 x 124 x 92 x 23	2 x 124 x 92 x 23	1 x 124 x 92 x 23	1 x 124 x 92x 23
TOTAL ELECTRIC POWER (KW)	39,6 KW (w/Steam-53,1KW)	27 ,4KW (w/Steam-36,4KW)	24,4 KW (w/steam-33,4KW)	12,2 KW (w/Steam-16,7KW)	12,2 KW (w/Steam-16,7KW)
POWER SUPPLY VOLTAGE (V)	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE
OPERATING FREQUENCY (Hz)	50/60	50/60	50/60	50/60	50/60
THERMOSTAT RANGE (°C)	50-400	50-400	50-400	50-400	50-400
POWER CORD mm (H07 RNFR)	5 x 4	5 x 4	5 x 4	5 x 4	5 x 4
PROTECTION CLASS	IP 20	IP 20	IP 20	IP 20	IP 20
NET WEIGHT (KG)	771 (w/Steam-822kg)	589 (w/Steam-623kg)	571 (w/Steam-605kg)	372 (w/Steam-389kg)	207 (w/Steam-224kg)
RATED CURRENT (A)	121	89	64	32	32
INSULATION	STONE WOOL	STONE WOOL	STONE WOOL	STONE WOOL	STONE WOOL
COOKING STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE	SHAMOT STONE
LIGHTING	6 x 25 W	4 x 25 W	4 x 25 W	2 x 25 W	2 x 25 W
CAPASITY(CM) (PER FLOOR)	40x60x 4 40x80x 3 40x40x 6 Ø 40x 6	40x80x3 40x60x4 40x40x6 Ø 40x6	40x80x3 40x60x4 40x40x6 Ø 40x6	40x80x3 40x60x4 40x40x6 Ø 40x6	40x80x3 40x60x4 40x40x6 Ø 40x6